



## *WinnerOne Comfort Exterior Emulsion*

HomeCoat's WinnerOne Comfort Exterior Emulsion is pure acrylic (100%) based exterior emulsion. The product have good bacterial, UV and excellent water resistance due to higher percentage of pure acrylic over competitors.

### ▪ **Key Features**

- ✚ High performance
- ✚ Durable coating
- ✚ Specially designed to withstand extreme climatic conditions of high rainfall, temperature extremes and high humidity
- ✚ It provides excellent bacterial and water resistance
- ✚ It gives Hard, Tough, Flexible & Glossy Film
- ✚ Excellent Wet Scrub & Abrasion
- ✚ Excellent pigment loading characteristics
- ✚ Alkali resistance.
- ✚ Its surfactant based technology helps to resist dirt formation on the surface.

### ▪ **Substrate Suitability**

WinnerOne Comfort Exterior Emulsion can be applied on vast range of exterior surfaces viz cement plaster, masonry.

A10, Balaji Industrial Estate,

Tondre Village, Taloja MIDC, Taloja

Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001

eMail: - [connect@homecoat.in](mailto:connect@homecoat.in)

Web: - [www.homecoat.in](http://www.homecoat.in)



## ▪ How To Use

### ✚ Surface Preparation

- Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algae / fungal growth or any other type of contamination.
- This can be achieved by vigorous brushing of surface with media like wire, tar brush etc and cleaning with soft water.
- In case of pre painted surfaces - loose old paint etc should be thoroughly removed.
- Surfaces showing signs of chalking and flaking should be treated with some suitable sealer etc.

### ✚ Touch Ups/Rectification

- Any touch up/ rectification required in the surface should be done with sand cement mortar only and it should be subjected to proper curing.
- For freshly plastered surface, care should be taken for proper curing and sufficient drying time.



## ■ Technical Data

<i>Property</i>	<i>Data</i>
<i>Covering**</i>	On normal masonry surface brush applied 170 sq ft per ltr
<i>Recommended Dry Film Thickness(DFT)</i>	60 - 70 microns for 2 coats
<i>Weight (Per Ltr)</i>	1.35+/-0.05
<i>PH</i>	9-10
<i>Thinning</i>	Vary surface to surface (Ideally between 40 – 60 %)
<i>Drying Time</i>	Touch Dry 1hr   Recoat : 4-6 hrs
<i>Shelf Life</i>	Minimum 1yr when stored in original sealed container away from sunlight and excessive heat.
<i>Pot Life</i>	24 hrs

\*\* Actual coverage may vary on factors such as substrate porosity, method of application etc.

## ■ Precautions

Before Use

- ✚ Do not over dilute or over extend the brush
- ✚ Stir Well Before Use

## ■ Post Application

For performance optimization - ensure proper washing and cleaning of structures at regular intervals.

## ■ Pack Sizes & Shade Range

- ✚ Pack Size Availability: 1ltr, 4ltr, 10ltr, 20ltr
- ✚ Available in Large Shade Range