



WinnerOne Comfort Interior Emulsion

HomeCoat's WinnerOne Comfort emulsion is a recommended quality solution for distemper users. It is a co polymer acrylic coating which provides a smooth finish with better fungus/algie resistance over distemper and longer life.







▪ **Key Features**

- ✚ WinnerOne Comfort Acrylic Emulsion is a co polymer emulsion paint that offers rich, elegant and smooth finish to the walls.
- ✚ It is much more durable than distemper (3-4 yrs of durability compared to recommended distemper durability of 2 yrs).
- ✚ The Emulsion provides a smooth finish with a marginal difference in total cost to a distemper (considering total coverage and longer durability).
- ✚ HomeCoat's WinnerOne Comfort Interior Emulsion is all weather, high performance, durable coating specially designed to withstand climatic conditions for the interior surfaces.
- ✚ It refrains surface from fungal/bacterial growth and have good water resistance.
- ✚ It makes surface tough & glossy.
- ✚ It's surfactant based technology helps resist dirt formation on the surface.



■ Substrate Suitability

HomeCoat's WinnerOne Comfort Interior Emulsion is compatible to the following substrates –

-  P O P
-  Gypsum
-  Gypsum board false ceilings
-  Asbestos sheets
-  Concrete
-  Plaster etc.

■ Technical Data

<i>Property</i>	<i>Data</i>
<i>Covering**</i>	On smooth primed masonry surface by brushing: 200-250 sq ft per ltr
<i>Drying time</i>	Surface Dry time ~ 10-15 minutes
<i>Volume Solids</i>	36+/-2
<i>Weight Per Ltr</i>	1.45+/-0.05
<i>PH</i>	8 to 9
<i>Touch Dry</i>	20 mins
<i>Shelf Life</i>	Minimum 1 year from date of manufacture in original sealed container
<i>Pot Life</i>	Use within 24 hrs

**Actual coverage may vary on factors such as substrate porosity, method of application etc. It is advisable and Strongly recommended to check the covering on respective surface before use.

A10, Balaji Industrial Estate,

Phone No: - +91 82 6001 3001

Tondre Village, Taloja MIDC, Taloja

eMail: - connect@homecoat.in

Dist. Raigad, Panvel, Maharashtra 410208

Web: - www.homecoat.in



■ Precautions

Before Use

- ✚ Do not over dilute or over extend the brush
- ✚ Stir Well Before Use

■ Post Application

- ✚ For removing stain, sponge clean with a mild soap solution and wipe clean. Ensure a drying time of 1 week before cleaning.
- ✚ No rigorous scrubbing.

■ Pack Sizes & Shade Range

- ✚ Pack Size Availability: 1ltr, 4ltr, 10ltr, 20ltr
- ✚ Available in Large Shade Range