### HOMECOAT (opc) Pvt Ltd

### "Your trusted partner"

A10, Balaji Industrial Estate, Tondre Village, Taloja MIDC, Taloja Dist. Raigad, Panvel, Maharashtra 410208 Phone No: - +91 82 6001 3001 eMail: - <u>connect@homecoat.in</u> Web: - www.homecoat.in



# WinnerOne IMPERIAL Interior Emulsion

HomeCoat'sWinnerOne IMPERIAL Interior Emulsion is pure acrylic (100%)emulsion.

### Key Features

- **4** Excellent Gloss and Coverage.
- \rm Long Life.
- **4** Excellent stain resistance.
- **4** Durable coating.
- ↓ It gives Hard, Tough, Flexible & Glossy Film.
- ↓ Easy to clean with spray water& sponge.

### Substrate Suitability

WinnerOne IMPERIAL Emulsion can be applied on vast range of interior surfaces. The correction procedure of application is as follows, to get best results.

#### How To Use

#### Surface Preparation

- Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algea / fungal growth or any other type of contamination.
- This can be achieved by vigorous brushing of surface with media like wire, tar brush etc and cleaning with soft water.

## HOMECOAT (opc) Pvt Ltd

A10, Balaji Industrial Estate, Tondre Village, Taloja MIDC, Taloja Dist. Raigad, Panvel, Maharashtra 410208 Phone No: - +91 82 6001 3001 eMail: - <u>connect@homecoat.in</u> Web: - www.homecoat.in

## "Your trusted partner"



- In case of pre painted surfaces loose old paint etc should be thoroughly removed.
- Surfaces showing signs of chalking and flaking should be treated with some suitable sealer etc.

#### **4** Touch Ups/Rectification

- For freshly plastered surface, care should be taken for proper curing and sufficient drying time.
- Apply two coats of WinnerOne Comfort Cement/Acrylic Putty. In case of cement putty, use scrubbing to achieve better finish on the walls.
- Apply one coat of WinnerOne Reliable Water Primer.

### Technical Data

Property	Data
Covering**	On normal masonry surface brush applied
	100-120 sqft per ltr
Recommended Dry	50 - 60 microns for 2 coats

Reg Of: - 101, PrabhuKripa, Plt no 10&12, Rd no 13, Sect 19, New Panvel, Raigad 410206 CIN: - U74999MH2017OPC293941

## HOMECOAT (opc) Pvt Ltd

## "Your trusted partner"

A10, Balaji Industrial Estate, Tondre Village, Taloja MIDC, Taloja Dist. Raigad, Panvel, Maharashtra 410208 Phone No: - +91 82 6001 3001 eMail: - <u>connect@homecoat.in</u> Web: - www.homecoat.in



Film Thickness(DFT	`)
Weight (Per Ltr)	1.30+/-0.05
РН	8 to 9
Thinning	40-45% by volume with water
Drying Time	Touch Dry 1hr   Recoat : 4-6 hrs
Shelf Life	Minimum 1 yr when stored in original sealed container away
	from sunlight and excessive heat.
Pot Life	24 hrs

\*\* Actual coverage may vary on factors such as substrate porosity, method of application etc.

#### Precautions

Before Use

- ↓ Do not over dilute or over extend the brush
- ♣ Stir Well Before Use

#### Post Application

For performance optimization - ensure proper washing and cleaning of structures at regular intervals.

#### Pack Sizes & Shade Range

4 Pack Size Availability: 11tr, 41tr, 101tr, 201tr