



## WinnerOne Metallic Texture

HomeCoat's WinnerOne Metallic texture is pure acrylic (100%) based texture applicable for exterior/interior surfaces. The product has good bacterial, UV and excellent water, weather resistance due to higher percentage of pure acrylic. The product has excellent shine matching to enamel level or higher.

### ■ Key Features

- ✚ Water based product with excellent shine
- ✚ High gloss product eliminates need of an additional layer of lacquer for higher sheen in the statue painting.
- ✚ It provides multiple effects such as Crinkle, Dapple, Weaving, Canvas, Spatula, Colorwash, Ragging, Sponging, Combing using specialized tools.
- ✚ Easy brush ability.
- ✚ Smooth finish.
- ✚ Durable coating-Abrasion resistant.
- ✚ Specially designed to withstand the extreme climatic conditions of high rainfall, temperature extremes and high humidity.
- ✚ It gives Hard, Tough, Flexible & Glossy Film.
- ✚ Excellent Wet Scrub & Abrasion.
- ✚ Excellent pigment loading characteristics.
- ✚ Alkali resistance.

### ■ Substrate Suitability



WinnerOneMetallic Texture can be applied on vast range of surfaces vizsuch as internal walls, moulds, metals, marble surface and statues.

## ■ How To Use

### ✚ Surface Preparation

- Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algae / fungal growth or any other type of contamination..
- In case of pre painted surfaces - loose old paint etc should be thoroughly removed.
- Surfaces showing signs of chalking and flaking should be treated with some suitable sealer etc.
- Apply two coats of WinnerOne Comfort Cement/Acrylic Putty. In case of cement putty, use scrubbing to achieve better finish on the walls.
- Apply one coat of WinnerOne Reliable Water Primer.
- Apply two coat of Imperial luxury emulsion.
- Apply one of metallic texture-Gold, with dilution as needed. Use special tools to create special effects on the surface.

## ■ Technical Data

Property	Data
Recommended Dry Film Thickness(DFT)	50 - 60 microns for 2 coats
Weight (Per Ltr)	1.10+/-0.05

# HOME COAT (opc) Pvt Ltd

“Your trusted partner”

A10, Balaji Industrial Estate,  
Tondre Village, Taloja MIDC, Taloja  
Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001  
eMail: - [connect@homecoat.in](mailto:connect@homecoat.in)  
Web: - [www.homecoat.in](http://www.homecoat.in)



<b>PH</b>	9-10
<b>Drying Time</b>	Touch Dry 1hr   Recoat : 4-6 hrs
<b>Shelf Life</b>	Minimum 1yr when stored in original sealed container away from sunlight and excessive heat.
<b>Pot Life</b>	24 hrs

\*\* Actual coverage may vary on factors such as substrate porosity, method of application etc.

## ■ Precautions

Before Use

- ✚ Do not over dilute or over extend the brush
- ✚ Stir Well Before Use

## ■ Post Application

For performance optimization - ensure proper washing and cleaning of structures at regular intervals.

## ■ Pack Sizes

- ✚ Pack Size Availability: 50 ml, 100 ml, 200 ml, 500 ml, 1ltr, 4ltr, 10ltr, 20ltr.