



## *WinnerOne Reliable Acrylic Putty*

HomeCoat water based Acrylic Wall Putty is a ready-to-use putty meant for filling out cracks and dents, and smoothen the plastered wall or similar interior surfaces. It provides strong, durable foundation and brings out the best performance from the finish paints, both in looks and in durability. It has excellent sheen with superior waterproofing capability, which helps improve life of interior paint.

### ▪ **Key Features**

- ✚ Special acrylic binders ensure that the putty retains a strong grip on the wall surface, thus increasing the life of the paint film.
- ✚ Extremely smooth and consistent
- ✚ .Emulsions painted over acrylic putty looks richer in color and appearance.
- ✚ Quick Drying
- ✚ Better Alkali resistance
- ✚ Superior Sheen
- ✚ Best finish

### ▪ **Substrate Suitability**

HomeCoat's WinnerOne Acrylic Putty is compatible to the following substrates –

- ✚ POP
- ✚ Gypsum
- ✚ Gypsum board false ceilings
- ✚ Asbestos sheets, concrete
- ✚ Plaster etc.



## ■ Technical Data

Property	Data
Application Method	Putty knife
Covering**	5-6 sqft per kg (double coat)
Finish	Smooth
PH	8 to 9
Thinning	Ready to use, or 3-5% depending on the application.
Drying Time	Dry to touch 30 minutes
Shelf Life	Minimum 6 months in original packaging away from direct sunlight and excessive heat
Recommended DFT	0.5 – 1.0 mm

\*\*Actual coverage may vary on factors such as substrate porosity, method of application etc.  
It is advisable and strongly recommended to check the covering on respective surface before use.

## ■ Surface Preparation

- ✚ Ensure that the surface to be painted is free from any loose paint, dust or grease.
- ✚ Any previous growth of fungus, algae or moss needs to be removed thoroughly by vigorous wire brushing and cleaning with water.
- ✚ On fungus affected areas apply a coat of 'Bio Wash' solution.
- ✚ Allow it to dry for 4-6 hours and then wash with water.



### ▪ **Direction For Use**

- ✚ Apply WinnerOne Acrylic Putty by putty patra or spray. Moisten the wall and apply one coat of putty with the help of a putty knife.
- ✚ Draw the blade from bottom to top while applying the putty. Make the surface smooth using water paper no. 400 or a soft wet cloth.
- ✚ Cut the surface and apply another coat after 3-4 hours.
- ✚ Clean the surface to give a final thickness of 1.5 mm, using emery paper no. 400.
- ✚ Clean the cut surface with soft wet cloth or wet sponge and allow 3 days before applying the top coat.

### ▪ **Precautions**

- ✚ Prior to use, read and follow product specification, MSDS and label information.
- ✚ Do not over thin
- ✚ Do not apply WinnerOne Acrylic Putty in the form of single coat or thick layer application.
- ✚ Avoid contact with eyes and skin.
- ✚ Use safety equipment like rubber or polythene gloves, safety goggles / glasses and face masks

### ▪ **Pack Sizes & Shade Range**

- ✚ Pack Size Availability: 20Kg