



## *WinnerOne Reliable Exterior Emulsion*

HomeCoat's WinnerOne Reliable Exterior Emulsion is pure acrylic (100%) based exterior emulsion. The product has good bacterial, UV and excellent water resistance due to higher percentage of pure acrylic.

### ■ **Key Features**

- ✚ Excellent hide, easy brushability.
- ✚ Smooth finish and good shine.
- ✚ Durable coating.
- ✚ Specially designed to withstand extreme climatic conditions of high rainfall, temperature extremes and high humidity.
- ✚ It provides excellent bacterial and water resistance.
- ✚ It gives Hard, Tough, Flexible & Glossy Film.
- ✚ Excellent Wet Scrub & Abrasion.
- ✚ Excellent pigment loading characteristics.
- ✚ Alkali resistance.
- ✚ Its surfactant based technology helps to resist dirt formation on the surface.
- ✚ Easy to clean with spray water.

### ■ **Substrate Suitability**

WinnerOne Comfort Exterior Emulsion can be applied on vast range of exterior surfaces viz cement plaster, masonry.



### ▪ **How To Use**

#### **Surface Preparation**

- Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algae / fungal growth or any other type of contamination.
- This can be achieved by vigorous brushing of surface with media like wire, tar brush etc and cleaning with soft water.
- In case of pre painted surfaces - loose old paint etc should be thoroughly removed.
- Surfaces showing signs of chalking and flaking should be treated with some suitable sealer etc.

#### **Touch Ups/Rectification**

- Any touch up/ rectification required in the surface should be done with sand cement mortar only and it should be subjected to proper curing.
- For freshly plastered surface, care should be taken for proper curing and sufficient drying time.





## ■ Technical Data

<i>Property</i>	<i>Data</i>
<i>Covering**</i>	On normal masonry surface brush applied 50-60 sqft per ltr
<i>Recommended Dry Film Thickness(DFT)</i>	50 - 60 microns for 2 coats
<i>Weight (Per Ltr)</i>	1.20+/-0.05
<i>PH</i>	8 to 9
<i>Thinning</i>	35-40% by volume with water
<i>Drying Time</i>	Touch Dry 1hr   Recoat : 4-6 hrs
<i>Shelf Life</i>	Minimum 1yr when stored in original sealed container away from sunlight and excessive heat.
<i>Pot Life</i>	24 hrs

\*\* Actual coverage may vary on factors such as substrate porosity, method of application etc.

## ■ Precautions

Before Use

-  Do not over dilute or over extend the brush
-  Stir Well Before Use

## ■ Post Application

For performance optimization - ensure proper washing and cleaning of structures at regular intervals.

## HOMECOAT (opc) Pvt Ltd

---

A10, Balaji Industrial Estate,

Tondre Village, Taloja MIDC, Taloja

Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001

eMail: - [connect@homecoat.in](mailto:connect@homecoat.in)

Web: - [www.homecoat.in](http://www.homecoat.in)



*“Your trusted partner”*

### ▪ Pack Sizes & Shade Range

✚ Pack Size Availability: 1ltr, 4ltr, 10ltr, 20ltr

✚ Available in Large Shade Range