



WinnerOne ReliableX Exterior Emulsion

HomeCoat’s WinnerOne ReliableX Exterior Emulsion is pure acrylic (100%) based exterior emulsion. The product has good bacterial, UV and excellent water, weather resistance due to higher percentage of pure acrylic.

■ **Key Features**

- ✚ Excellent hide, coverage easy brush ability.
- ✚ Smooth finish and good shine.
- ✚ Durable coating.
- ✚ Water repellent film deters wetting of the surface.
- ✚ Specially designed to withstand extreme climatic conditions of high rainfall, temperature extremes and high humidity.
- ✚ It provides excellent bacterial and water resistance.
- ✚ It gives Hard, Tough, Flexible & Glossy Film.
- ✚ Excellent Wet Scrub & Abrasion.
- ✚ Excellent pigment loading characteristics.
- ✚ Alkali resistance.
- ✚ Its surfactant based technology helps to resist dirt formation on the surface.

■ **Substrate Suitability**

WinnerOneReliableX Exterior Emulsion can be applied on vast range of exterior surfaces viz cement plaster, masonry.



■ How To Use

✚ Surface Preparation

- Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algae / fungal growth or any other type of contamination.
- This can be achieved by vigorous brushing of surface with media like wire, tar brush etc and cleaning with soft water.
- In case of pre painted surfaces - loose old paint etc should be thoroughly removed.
- Surfaces showing signs of chalking and flaking should be treated with some suitable sealer etc.

✚ Touch Ups/Rectification

- Any touch up/ rectification required in the surface should be done with sand cement mortar only and it should be subjected to proper curing.
- For freshly plastered surface, care should be taken for proper curing and sufficient drying time.

■ Technical Data

Property	Data
Covering**	On normal masonry surface brush applied 60-70 sqft per ltr double coat.
Recommended Dry Film Thickness(DFT)	50 - 60 microns for 2 coats
Weight (Per Ltr)	1.25+/-0.05

HOME COAT (opc) Pvt Ltd

“Your trusted partner”

A10, Balaji Industrial Estate,
Tondre Village, Talaja MIDC, Talaja
Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001
eMail: - connect@homecoat.in
Web: - www.homecoat.in



PH	9-10
Thinning	40-45% by volume with water
Drying Time	Touch Dry 1hr Recoat : 4-6 hrs
Shelf Life	Minimum 1yr when stored in original sealed container away from sunlight and excessive heat.
Pot Life	24 hrs

** Actual coverage may vary on factors such as substrate porosity, method of application etc.

■ Precautions

Before Use

- ✚ Do not over dilute or over extend the brush
- ✚ Stir Well Before Use

■ Post Application

For performance optimization - ensure proper washing and cleaning of structures at regular intervals.

■ Pack Sizes & Shade Range

- ✚ Pack Size: 1ltr, 4ltr, 10ltr, 20ltr
- ✚ Available in Large Shade Range