



WinnerOneSuperGlossExterior Emulsion

HomeCoat's WinnerOneSuperGlossExterior Emulsion is pure acrylic (100%) based emulsion applicable for interior surfaces. The product has good bacterial, UV and excellent water, weather resistance due to higher percentage of pure acrylic. The product has excellent shine matching to enamel level or higher. It has variety of applications in specialist requirements, such as Statue paintings.

■ Key Features

- ✚ Water based product with excellent shine matching to or higher than oil based enamel.
- ✚ Water based high gloss product eliminates need of an additional layer of lacquer for higher sheen in the statue painting.
- ✚ Excellent hide, easy brush ability.
- ✚ Smooth finish.
- ✚ Durable coating.
- ✚ Specially designed to withstand the extreme climatic conditions of high rainfall, temperature extremes and high humidity.
- ✚ It gives Hard, Tough, Flexible & Glossy Film.
- ✚ Excellent Wet Scrub & Abrasion.
- ✚ Excellent pigment loading characteristics.
- ✚ Alkali resistance.

■ Substrate Suitability



WinnerOneSuper Gloss Exterior Emulsion can be applied on vast range of surfaces vizsuch as internal walls, moulds, metals, marble surface, and statues.

■ How To Use

✚ Surface Preparation

- Ensure that the substrate to be painted is free of any dirt, dust, oil, grease, any algae / fungal growth or any other type of contamination..
- In case of pre painted surfaces - loose old paint etc should be thoroughly removed.
- Surfaces showing signs of chalking and flaking should be treated with some suitable sealer etc.

■ Technical Data

Property	Data
Covering**	On normal surface brush applied 100-130sqft per ltr double coat.
Recommended Dry Film Thickness(DFT)	50 - 60 microns for 2 coats
Weight (Per Ltr)	1.10+/-0.05
PH	9-10
Thinning	40-45% by volume with water
Drying Time	Touch Dry 1hr Recoat : 4-6 hrs
Shelf Life	Minimum 1yr when stored in original sealed container away

HOME COAT (opc) Pvt Ltd

A10, Balaji Industrial Estate,
Tondre Village, Taloja MIDC, Taloja
Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001
eMail: - connect@homecoat.in
Web: - www.homecoat.in

“Your trusted partner”



	from sunlight and excessive heat.
Pot Life	24 hrs

** Actual coverage may vary on factors such as substrate porosity, method of application etc.

■ Precautions

Before Use

- ✚ Do not over dilute or over extend the brush
- ✚ Stir Well Before Use

■ Post Application

For performance optimization - ensure proper washing and cleaning of structures at regular intervals.

■ Pack Sizes & Shade Range

- ✚ Pack Size Availability: 250 ml, 500 ml, 1ltr, 4ltr, 10ltr, 20ltr
- ✚ Available in shades – **White & Black.**