



WinnerOne WaterPruff Smart Paint

HomeCoat's WinnerOne WaterPruff Smart Paint is an elastomeric waterproofing coating with PP fiber reinforced. It is an excellent waterproofing and dampproofing solution for terraces, chajjas and dead walls. The product has excellent elasticity and crack bridging. Fiber mesh increases film strength and stain resistance.

▪ **Key Features**

- ✚ Excellent crack building ability.
- ✚ Durable coating.
- ✚ Anti-algae and anti-fungal properties.
- ✚ Acid Resistant.
- ✚ High abrasion resistance due to high strength PP fibers.
- ✚ Excellent crack bridging due to elastomeric nature.
- ✚ Specially designed to withstand extreme climatic conditions of high rainfall, temperature extremes and high humidity.
- ✚ High breathability.
- ✚ High sheen, brilliant white color and thick layer enable heat reflectance.
- ✚ Non-toxic in nature.
- ✚ Easy to Recoat.

▪ **Substrate Suitability**

WinnerOne WaterPruff Smart Paint is suitable on terraces, chajjas, building roofs, sunshades and external vertical walls.



■ How To Use

✚ Surface Preparation

- Ensure that the substrate is free of any dirt, dust, oil, grease, any algae / fungal growth or any other type of contamination.
- This can be achieved by vigorous brushing of surface with media like wire, tar brush etc and cleaning with soft water.
- Small cracks upto 3mm or less should be opened, cleaned and filled with crack filler. Bigger cracks, damaged portions and hollow areas must be repaired.

✚ Application Procedure

To get best results, the application procedure plays an important role.

➤ Vertical surface (Building Walls)

- Apply WinnerOne WaterPruff Smart Paint (3:1 dilution ratio) on the application surface using roller.
- Let the surface dry for 6 hrs.
- Apply WinnerOne WaterPruff Smart Paint (Zero dilution) on the application surface using roller.
- Let the surface dry for 6 hrs.
- Apply two coats of approved HomeCoat Topcoat on the surface.

➤ Horizontal Surface (Terrace, Chajjas)

HOME COAT (opc) Pvt Ltd

A10, Balaji Industrial Estate,
Tondre Village, Talaja MIDC, Talaja
Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001
eMail: - connect@homecoat.in
Web: - www.homecoat.in

“Your trusted partner”



- Apply WinnerOne WaterPruff Smart Paint (3:1 dilution ratio) on the application surface using roller.
- Let the surface dry for 6 hrs.
- Apply WinnerOne WaterPruff Smart Paint (Zero dilution) on the application surface using roller.
- Let the surface dry for 6 hrs.
- Apply **again** WinnerOne WaterPruff Smart Paint (Zero dilution) on the application surface using roller.

■ Technical Data

Property	Data
Covering**	On normal masonry surface roller to be applied 1.) Vertical Surface 45 sq ft/ ltr 2.) Horizontal Surface 25 sq ft/ltr (Double Coat)
Recommended Dry Time Touch	4-6 Hrs
Weight (Per Ltr)	1.20+/-0.05
PH	9-10
Thinning	30% by volume with water for self-priming 0% dilution for application
Drying Time	Touch Dry 1hr Recoat : 4-6 hrs
Shelf Life	Minimum 1yr when stored in original sealed container away from sunlight and excessive heat.
Pot Life	24 hrs

HOMECOAT (opc) Pvt Ltd

A10, Balaji Industrial Estate,

Tondre Village, Taloja MIDC, Taloja

Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001

eMail: - connect@homecoat.in

Web: - www.homecoat.in



“Your trusted partner”

** Actual coverage may vary on factors such as substrate porosity, method of application etc.

■ **Precautions**

Before Use

- ✚ Do not over dilute or over extend the brush
- ✚ Stir Well Before Use

■ **Post Application**

For performance optimization - ensure proper washing and cleaning of structures at regular intervals.

■ **Pack Size**

- ✚ Pack Size Availability: 20ltr