



WinnerOne Anticorrosive Paint (Water based)

HomeCoat's WinnerOne water based anticorrosive paint is a water thinnable alkyd emulsion. It shows good penetration on metal substrates and shows very high gloss. It is water thinnable & formulated to seal the base surface. It gives glossy look on all types of substrates and gives an elegant look.

▪ **Key Features**

- ✚ Very easy for application.
- ✚ Being water base it saves extra cost of thinner for dilution.
- ✚ Applies with two layers for all types of metal surfaces.
- ✚ Excellent durability..
- ✚ Excellent gloss.
- ✚ Soap & water cleanup.
- ✚ Lead free.

▪ **Substrate Suitability**

WinnerOne water based anticorrosive paint is compatible to the following substrates - metal & wood etc.

▪ **How To Use**

- ✚ Surface Preparation.
- ✚ Clean the surface properly.
- ✚ Ensure that the substrate to be painted is free of any dirt, dust, rust, oil, grease, or any other type of contamination.

HOME COAT (opc) Pvt Ltd

“Your trusted partner”

A10, Balaji Industrial Estate,

Phone No: - +91 82 6001 3001

Tondre Village, Taloja MIDC, Taloja

eMail: - connect@homecoat.in

Dist. Raigad, Panvel, Maharashtra 410208

Web: - www.homecoat.in



- ✚ In case of pre-painted surfaces - loose old paint etc. should be thoroughly removed.
- ✚ Apply single coat of metal primer.
- ✚ Apply two coats of WinnerOne Anticorrosive paint with overnight duration.

■ Technical Data

| Property | Data |
|-------------------|--|
| Shade | As per specified shade |
| Aspect within pot | Viscous liquid |
| Density | 1+/- 0.1 |
| Finish | Glossy |
| Gloss | 80+ for 60 degree angle |
| Drying time | Touch Dry : 2 hrs Tack Dry : 6 hrs Hard Dry : 24 hrs |
| Solvent | DM Water |
| Dilution | 10-15% |
| Coverage | 100 sq ft two coats |
| Shelf Life | 12 months when stored in cool & dry place in original sealed container |
| Binder | Alkyd |
| Salt Sprey Result | 1000 hrs. |

** The actual covering may vary depending on the condition of surface & method of application

HOMECOAT (opc) Pvt Ltd

A10, Balaji Industrial Estate,

Tondre Village, Taloja MIDC, Taloja

Dist. Raigad, Panvel, Maharashtra 410208

Phone No: - +91 82 6001 3001

eMail: - connect@homecoat.in

Web: - www.homecoat.in

“Your trusted partner”



▪ **Precautions**

- ✚ Do not over thin or overextend the brush
- ✚ Stir well & strain before use.
- ✚ Ensure the moisture content on the surface is below 12%.
- ✚ Ensure the ph of the surface is between 7-11.

▪ **Post Painting Care**

- ✚ For best performance of Paint, ensure proper washing and cleaning of all algae and fungal growth, if any, at regular intervals of six months.

▪ **Pack Sizes**

- ✚ Pack Size Availability: 1 ltr, 4 ltr, 10 ltr, 20 ltr.